



MSR + IC + NFC

High-Capacity Battery













Restaurant

Hotel

Parking lot Gas station

## ePayPOS600

## **SPECIFICATIONS**

OS Compatibility	Android, Apple iOS and Windows Mobile
Processor	32-bit RISC Core
Memory	64KB RAM, 512KB FLASH
Display	1.4 inch, 128 × 64, Mono
Bluetooth	BR/EDR V3.0 + BLE4.2
NFC	13.56MHz, ISO/IEC 14443, ISO18092, Type A&B, Felica, Mifare card
MSR	ISO/IEC 7811, ISO/IEC 7813, Track 1/2/3, Bi-directional swiping
IC	ISO/IEC 7816, Conform to EMV L1/L2
Keypad	5 × 3 PIN pad 15 keys
Battery	Li-ion battery 500 mAh / 3.7V
Charging	Micro USB2.0
Dimensions	113.6 mm(L) × 59 mm(W) × 14 mm(H)
Weight	80g
Environmental	Working temperature: 0 °C $\sim$ +45 °C / 5 $\sim$ 95% RH Storage temperature: -10 °C $\sim$ +60 °C / 5 $\sim$ 95% RH
Certification	PCI 4.0, EMV L1&L2, EMV Contactless L1 Paypass, payWave, AMEX ExpressPay, Discover, Quics, JCB, Pure, TQM FCC, CE, RoHS, WEEE





























